

Optical Fiber Adapter(FC,SC,ST,LC)

Features	
Low Insertion Loss High Repeatability	
Application	
LAN, Data network CATV Network Telecommunication	

Specifications:

Insertion Loss	≤0.2 dB
Plug and unplug force (g/f)	200-600
Durability	1000times
Operating Temperature	-40℃ to +75℃

PN	Description	Photo
AD-FC/SM-SP01	FC/PC adaptor (Small D-type)	 <p>FC Small D Adapter</p>
AD-FC/SM-SP02	FC/PC adaptor (Big D-type)	 <p>Big D type FC Adapter</p>
AD-FC/SM-SP03	FC/PC adaptor (Solid)	
AD-FC/SM-SP04	FC/PC adaptor (2 body)	

AD-FC/SM-SP05	FC/PC adaptor (Oval)	A metal FC/PC adaptor with an oval-shaped PC connector and an FC connector.
AD-FC/SM-SP06	FC/PC adaptor (Rectangular)	A metal FC/PC adaptor with a rectangular PC connector and an FC connector, shown with two green protective caps.
AD-SC/SM-SP01	SC/PC Simplex Adapter	A white SC/PC simplex adapter and a blue SC/PC simplex adapter.
AD-SC/SM-SP02	SC/PC Duplex Adapter	A blue SC/PC duplex adapter.
AD-SC/SM-SP03	SC/APC Simplex Adapter	A green SC/APC simplex adapter.
AC-LC/SM-SP01	LC/PC simplex adapter	A blue LC/PC simplex adapter.

AC-LC/SM-SP02	LC/PC Duplex adapter	
AD-LC/SM-SP04	LC/APC Simplex Adapter	
AD-ST/SM-SP01	ST/PC Simplex adapter	
AD-MPO/SM-SP01	MPO Adapter	