

3x3 Monolithic Single Mode Coupler

Features	
Low excess loss & low IL Mini Size High stability and reliability	
Application	
Optical communication systems Testing instrument Optical fiber sensors	

Specifications

Parameter	Type	3x3 CP-S		1x3 CP-W	
Operating wavelength (nm)		1310, 1550,		1310/1550	
Operating bandwidth (nm)		±15		±40	
Grade		P	A	P	A
Typical excess loss (dB)		0.1	0.15	0.1	0.15
Insertion loss (dB)		≤5.6	≤5.8	≤5.8	≤6.2
PDL(dB)		≤0.25	≤0.3	≤0.25	≤0.3
Uniformity (dB)		≤1.0	≤1.4	≤1.3	≤1.6
Directivity (dB)		≥55			
Operating temperature (°C)		-40 ~ +85			

Package Information

Configuration	3x3	
Fiber length	1m, others on request	
Fiber Type	SMF-28e	
Pigtail type	250μm bare fiber	900μm loose tube
Dimensions(mm)	φ3.0×54 or φ3.0×35 φ3.0×30	φ4.0×75

Ordering Information

CP	Wavelength	Grade	Port Type	Wavelength (nm)	Coupling Ratio	Pigtail Type	Fiber Type	Length	Connector	Package
	S = Single mode standard coupler W =Wide band coupler D =Dual window coupler T =Three Window coupler M =Multimode fiber Coupler	P	1x2	532	1/99	250=250um	1=SMF-28e	1=	NE=None	3x54
		A	2x2	633	2/98	bare fiber	2=50/125	1m	FA=FC/APC	3x40
			1x3	780	3/97	900=900um	3=62.5/12.5	X:other	FC=FC/UPC
			1x4	850	loose tube	4=HI1060FLE		SA=SC/APC	
			1x5	980	50/50	2000=2mm	X		SC=SC/UPC	
			1064		loose tube	5=Panda fiber		LC=LC/UPC	
				1310		3000=3mm	6=RC Fiber		LA=LC/APC	
				1550		loose tube	7=Others		MU=MU/UPC	
				1310/1550					C	
				1260~1620					XX=Others	