

## Optical Fiber Adapter(FC,SC,ST,LC)

<b>Features</b>	
Low Insertion Loss High Repeatability	
<b>Application</b>	
LAN, Data network CATV Network Telecommunication	

### Specifications:

Insertion Loss	≤0.2 dB
Plug and unplug force (g/f)	200-600
Durability	1000times
Operating Temperature	-40℃ to +75℃

PN	Description	Photo
AD-FC/SM-SP01	FC/PC adaptor (Small D-type)	 <p>FC Small D Adapter</p>
AD-FC/SM-SP02	FC/PC adaptor (Big D-type)	 <p>Big D type FC Adapter</p>
AD-FC/SM-SP03	FC/PC adaptor (Solid)	
AD-FC/SM-SP04	FC/PC adaptor (2 body)	

<b>AD-FC/SM-SP05</b>	<b>FC/PC adaptor (Oval)</b>	A metal FC/PC adaptor with an oval-shaped PC connector and an FC connector.
<b>AD-FC/SM-SP06</b>	<b>FC/PC adaptor (Rectangular)</b>	A metal FC/PC adaptor with a rectangular PC connector and an FC connector, shown with two green dust caps.
<b>AD-SC/SM-SP01</b>	<b>SC/PC Simplex Adapter</b>	A white SC/PC simplex adapter and a blue SC/PC simplex adapter.
<b>AD-SC/SM-SP02</b>	<b>SC/PC Duplex Adapter</b>	A blue SC/PC duplex adapter.
<b>AD-SC/SM-SP03</b>	<b>SC/APC Simplex Adapter</b>	A green SC/APC simplex adapter.
<b>AC-LC/SM-SP01</b>	<b>LC/PC simplex adapter</b>	A blue LC/PC simplex adapter.

<b>AC-LC/SM-SP02</b>	<b>LC/PC Duplex adapter</b>	
<b>AD-LC/SM-SP04</b>	<b>LC/APC Simplex Adapter</b>	
<b>AD-ST/SM-SP01</b>	<b>ST/PC Simplex adapter</b>	
<b>AD-MPO/SM-SP01</b>	<b>MPO Adapter</b>	